

Specifications

Model No.		AUXD18LALH	AUXD24LALH	AUXA30LALH	AUXA36LALH	AUXA45LALH	AUXA54LALH	
Power source		V/ø/Hz	1Ø, 230V ~, 50Hz					
Capacity	Cooling	kW	5.6	7.1	9.0	11.2	12.5	14.0
	Heating		6.3	8.0	10.0	12.5	14.0	16.0
Input power		W	39	46	59	80	99	119
Air flow rate	High	m³/h	1,150	1,280	1,600	1,800	1,900	2,000
	Med		940	1,040	1,300	1,300	1,370	1,370
	Low		870	870	1,100	1,100	1,100	1,100
Sound pressure level	High	dB(A)	36	38	40	44	46	47
	Med		30	33	38	38	39	39
	Low		29	29	33	33	33	33
Dimensions (H x W x D)		mm	246 x 840 x 840		288 x 840 x 840			
Weight		kg	23		27			
Connection pipe diameter		Liquid (Flare)	ø9.52					
		Gas (Frare)	ø15.88		ø19.05			
		Drain	ø25 (I.D.) ; ø32 (O.D.)					
Grille (option)	Model name		UTG-UGYA-W (FUJITSU brand); UTG-UGGA-W (GENERAL brand)					
	Dimensions (H x W x D)	mm	50 x 950 x 950					
	Weight	kg	5.5					

Note : Specifications are based on the following conditions.

Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.

Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.

Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m.