

Specifications

Model name			AUXB07LALH	AUXB09LALH	AUXB12LALH	AUXB14LALH	AUXB18LALH	AUXB24LALH	
Power source			230V ~, 50Hz						
Capacity	Cooling	kW	2.2	2.8	3.6	4.5	5.6	7.1	
	Heating		2.8	3.2	4.1	5.0	6.3	8.0	
Input power		W	25	25	29	35	36	84	
Airflow rate	High	m ³ /h	540	550	600	680	710	1,030	
	Med		450	450	530	590	580	830	
	Low		350	350	390	390	400	450	
Sound pressure level	High	dB(A)	34	35	37	38	41	50	
	Med		30	30	34	34	35	44	
	Low		25	25	27	27	27	30	
Dimensions (H x W x D)		mm	245 x 570 x 570						
Weight		kg	15				17		
Connection pipe diameter	Liquid (Flare)	mm	ø6.35				ø9.52		
	Gas (Flare)		ø12.70				ø15.88		
	Drain		ø25 (I.D.) ; ø32 (O.D.)						
Grille(option)	Model name		UTG-UF*C-W						
	Dimensions (H x W x D)		50 x 700 x 700						
	Weight		2.6						

F* : FY (FUJITSU) ; FG(GENERAL)

Note : Specifications are based on the following conditions.

Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.

Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.

Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m. Voltage : 230 [V].