

Specifications

Model name			AUXB07GALH	AUXB09GALH	AUXB12GALH	AUXB14GALH	AUXB18GALH	AUXB24GALH	
Power source			230V ~, 50Hz						
Capacity	Cooling	kW	2.2	2.8	3.6	4.5	5.6	7.1	
	Heating		2.8	3.2	4.1	5.0	6.3	8.0	
Input power		W	25	25	29	35	36	84	
Airflow rate	High	m ³ /h (l/s)	540 (150)	550 (153)	600 (167)	680 (189)	710 (197)	1,030 (286)	
	Med		450 (125)	450 (125)	530 (147)	590 (164)	580 (161)	830 (231)	
	Low		350 (97)	350 (97)	390 (108)	390 (108)	400 (111)	450 (125)	
Sound pressure level	High	dB(A)	34	35	37	38	41	50	
	Med		30	30	34	34	35	44	
	Low		25	25	27	27	27	30	
Dimensions (H x W x D)		mm	245 x 570 x 570						
Weight		kg	15				17		
Connection pipe diameter	Liquid (Flare)	mm	ø6.35				ø9.52		
	Gas (Flare)		ø12.70				ø15.88		
	Drain hose		VP25[ø25(I.D.); ø32(O.U.)]						
Cassette Grille	Model name		UTG-UFYC-W						
	Dimensions (H x W x D)	mm	50 x 700 x 700						
	Weight	kg	2.6						

Note : Specifications are based on the following conditions.

Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.

Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.

Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m. Voltage : 230 [V].