

Specifications

| Model name | | | AB*A12LBTH | AB*A14LBTH | AB*A18LBTH | AB*A24LBTH |
|--------------------------|----------------|-------------------|-------------------------|------------|------------|------------|
| Power source | | | 230V ~, 50Hz | | | |
| Capacity | Cooling | kW | 3.6 | 4.5 | 5.6 | 7.1 |
| | Heating | | 4.0 | 5.0 | 6.3 | 8.0 |
| Input power | | W | 30 | 42 | 74 | 99 |
| Airflow rate | High | m ³ /h | 660 | 780 | 1,000 | 1,000 |
| | Med | | 570 | 640 | 720 | 820 |
| | Low | | 490 | 550 | 580 | 680 |
| Sound pressure level | High | dB(A) | 36 | 40 | 46 | 47 |
| | Med | | 32 | 36 | 39 | 42 |
| | Low | | 28 | 34 | 35 | 37 |
| Dimensions (H x W x D) | | mm | 199 x 990 x 655 | | | |
| Weight | | kg | 25 | 27 | | |
| Connection pipe diameter | Liquid (Flare) | mm | ø6.35 | | ø9.52 | |
| | Gas (Flare) | | ø12.70 | | ø15.88 | |
| | Drain | | ø25 (I.D.) ; ø32 (O.D.) | | | |

AB*: ABY(FUJITSU), ABH(GENERAL)

Note : Specifications are based on the following conditions.

Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.

Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.

Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m.

Voltage : 230 [V].