

Specifications

Model No.			ARXC36LATH	ARXC45LATH
Power source		V/ø/Hz	1Ø, 230V ~, 50Hz	
Capacity	Cooling	kW	11.2	12.5
	Heating		12.5	14.0
Input power		W	405	427
Air flow rate	High	m³/h	2,600	3,500
	Med		1,950	3,000
	Low		1,450	2,460
Static pressure range		Pa	100 to 200	100 to 250
Standard static pressure			100	100
Sound pressure level	High	dB(A)	45	49
	Med		38	45
	Low		32	42
Dimensions (H x W x D)		mm	400 x 1,050 x 500	
Weight		kg	45	47
Connection pipe diameter	Liquid (Flare)	mm	ø9.52 (Flare)	
	Gas (Frare)		ø19.05 (Flare)	
	Drain		ø25 (I.D.) ; ø32 (O.D.)	

Note : Specifications are based on the following conditions.

Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.

Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.

Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m.