

Specifications

Model name			ARXB24GALH	ARXB30GALH	ARXB36GALH	ARXB45GALH	ARXA24GALH	ARXA30GALH	ARXA36GALH	ARXA45GALH	
Power source			230V ~, 50Hz				230V ~, 50Hz				
Capacity	Cooling	kW	7.1	9.0	11.2	12.5	7.1	9.0	11.2	12.5	
	Heating		8.0	10.0	12.5	14.0	8.0	10.0	12.5	14.0	
Input power			W	145	198	253	338	190	188	312	312
Airflow rate	High	m ³ /h (l/s)	1,100 (306)	1,410 (392)	1,710 (475)	1,970 (547)	1,280 (356)	1,280 (356)	1,720 (478)	1,720 (478)	
	Med		920 (256)	1,280 (356)	1,600 (444)	1,790 (497)	1,210 (336)	1,210 (336)	1,670 (464)	1,670 (464)	
	Low		810 (225)	1,150 (319)	1,470 (408)	1,670 (464)	1,130 (314)	1,130 (314)	1,600 (444)	1,600 (444)	
Static pressure range			Pa	0 to 80	0 to 80	0 to 80	0 to 80	30 to 150	30 to 150	30 to 150	30 to 150
Standard static pressure				40	50	50	60	100	100	100	100
Sound pressure level	High	dB(A)	31	34	37	41	38	40	43	43	
	Med		27	32	35	38	36	38	41	41	
	Low		25	29	33	36	34	36	39	39	
Dimensions (H x W x D)			mm	270 x 1,135 x 700				270 x 1,135 x 700			
Weight			kg	39	42			39	42		
Connection pipe diameter	Liquid (Flare)	mm	ø9.52				ø9.52				
	Gas (Flare)		ø15.88		ø19.05		ø15.88		ø19.05		
	Drain hose		VP25[ø25(I.D.); ø32(O.U.)]				VP25[ø25(I.D.); ø32(O.U.)]				

Note : Specifications are based on the following conditions.

Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.

Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.

Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m.