

Specifications

Model name			ARXB07GALH	ARXB09GALH	ARXB12GALH	ARXB14GALH	ARXB18GALH	
Power source			230V ~, 50Hz					
Capacity	Cooling	kW	2.2	2.8	3.6	4.5	5.6	
	Heating		2.8	3.2	4.0	5.0	6.3	
Input power			46	55	63	90	96	
Airflow rate	High	m ³ /h (l/s)	370 (103)	440 (122)	590 (164)	800 (222)	890 (247)	
	Med		310 (86)	370 (103)	500 (139)	750 (208)	810 (225)	
	Low		280 (78)	340 (94)	450 (125)	700 (194)	730 (203)	
Static pressure range			0 to 50					
Standard static pressure			25					
Sound pressure level	High	dB(A)	29	31	30	33	36	
	Med		26	29	28	32	34	
	Low		24	27	25	30	30	
Dimensions (H x W x D)			217 x 663 x 595		217 x 953 x 595			
Weight			15		22		23	
Connection pipe diameter	Liquid (Flare)	mm	ø6.35				ø9.52	
	Gas (Flare)		ø12.70				ø15.88	
	Drain hose		VP25[ø25(I.D.); ø32(O.U.)]					

Note : Specifications are based on the following conditions.

Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.

Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.

Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m.