

Specifications

Model name			ARXB24LATH	ARXB30LATH	ARXB36LATH	ARXB45LATH	ARXA24LATH	ARXA30LATH	ARXA36LATH	ARXA45LATH	
Power source			230V ~, 50Hz				230V ~, 50Hz				
Capacity	Cooling	kW	7.1	9.0	11.2	12.5	7.1	9.0	11.2	12.5	
	Heating		8.0	10.0	12.5	14.0	8.0	10.0	12.5	14.0	
Input power			W	145	198	253	338	190	188	312	312
Airflow rate	High	m ³ /h	1,100	1,410	1,710	1,970	1,280	1,280	1,720	1,720	
	Med		920	1,280	1,600	1,790	1,210	1,210	1,670	1,670	
	Low		810	1,150	1,470	1,670	1,130	1,130	1,600	1,600	
Static pressure range			Pa	0 to 80	0 to 80	0 to 80	0 to 80	30 to 150	30 to 150	30 to 150	30 to 150
Standard static pressure				40	50	50	60	100	100	100	100
Sound pressure level	High	dB(A)	31	34	37	41	38	40	43	43	
	Med		27	32	35	38	36	38	41	41	
	Low		25	29	33	36	34	36	39	39	
Dimensions (H x W x D)			mm	270 x 1,135 x 700				270 x 1,135 x 700			
Weight			kg	43	45		43	45			
Connection pipe diameter	Liquid (Flare)	mm	ø9.52				ø9.52				
	Gas (Flare)		ø15.88		ø19.05		ø15.88		ø19.05		
	Drain		ø25 (I.D.) ; ø32 (O.D.)				ø25 (I.D.) ; ø32 (O.D.)				

Note : Specifications are based on the following conditions.

Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.

Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.

Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m.