

## Specifications

Model name			ARXD07GALH	ARXD09GALH	ARXD12GALH	ARXD14GALH	ARXD18GALH	ARXD24GALH
Power source			230V ~, 50Hz					
Capacity	Cooling	kW	2.2	2.8	3.6	4.5	5.6	7.1
	Heating		2.8	3.2	4.0	5.0	6.3	8.0
Input power			44	50	54	92	83	122
Airflow rate	High	m <sup>3</sup> /h (l/s)	550 (153)	600 (167)	600 (167)	800 (222)	940 (261)	1,330 (369)
	Med		490 (136)	550 (153)	510 (142)	710 (197)	840 (233)	1,240 (344)
	Low		440 (122)	480 (133)	450 (125)	610 (169)	750 (208)	1,100 (306)
Static pressure range			0 to 90		0 to 90	0 to 90	0 to 90	0 to 50
Standard static pressure			25	25	25	25	25	25
Sound pressure level	High	dB(A)	28	29	30	34	34	35
	Med		25	26	27	32	32	32
	Low		22	24	24	28	28	29
Dimensions (H x W x D)			198 x 700 x 620				198 x 900 x 620	198 x 1,100 x 620
Weight			17		18		22	26
Connection pipe diameter	Liquid (Flare)	mm	ø6.35				ø9.52	
	Gas (Flare)		ø12.70				ø15.88	
	Drain hose		VP25[ø25(I.D.); ø32(O.U.)]					

Note : Specifications are based on the following conditions.

Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.

Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.

Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m.