

**Compact**



Model No.	Indoor Unit			AUAG12LV	AUAG18LV
Power Source		V/Ø/Hz	230 / 1 / 50	230 / 1 / 50	
Air Circulation	High	m³/h	600	680	
	Med		530	580	
	Low		470	490	
	Quiet		410	410	
Sound Pressure Level	Cooling   H/M/L/Q	dB(A)	37 / 34 / 30 / 27	38 / 34 / 30 / 26	
Net Dimension H x W x D		mm	245 x 570 x 570	245 x 570 x 570	
Weight		kg/lbs	15 (33)	15 (33)	
Piping Connections	Liquid Ø	mm (in)	Ø6.35 (1/4)	Ø6.35 (1/4)	
	Gas Ø		Ø9.52 (3/8)	Ø12.7 (1/2)	
Remote Control			Wired / Wireless	Wired / Wireless	

**Optional Parts:**

Wired Remote Controller: UTB-YUD  
 Fresh Air Intake Kit: UTZ-VXAA



Model No.	Indoor Unit			AUAG24LR	AUAG30LRLA	AUAG36LRLC-A	AUAG36LRLD-A	AUAG45LRLD-A
Power Source		V/Ø/Hz	230 / 1 / 50	230 / 1 / 50	230 / 1 / 50	230 / 1 / 50	230 / 1 / 50	230 / 1 / 50
Air Circulation	High	m³/h	1,600	1,600	1,900	2,000	2,000	
	Med		1,400	1,400	1,640	1,650	1,650	
	Low		1,270	1,270	1,460	1,460	1,460	
	Quiet		1,150	1,150	1,250	1,300	1,300	
Sound Pressure Level	Cooling   H/M/L/Q	dB(A)	40 / 38 / 36 / 32	40 / 38 / 36 / 32	43 / 38 / 36 / 32	46 / 42 / 39 / 35	46 / 42 / 39 / 35	
Net Dimension H x W x D		mm	288 x 840 x 840	288 x 840 x 840	288 x 840 x 840	288 x 840 x 840	288 x 840 x 840	
Weight		kg/lbs	23 (51)	23 (51)	26 (58)	29 (64)	29 (64)	
Piping Connections	Liquid Ø	mm (in)	Ø9.52 (3/8)	Ø9.52 (3/8)	Ø9.52 (3/8)	Ø9.52 (3/8)	Ø9.52 (3/8)	
	Gas Ø		Ø15.88 (5/8)	Ø15.88 (5/8)	Ø15.88 (5/8)	Ø15.88 (5/8)	Ø15.88 (5/8)	
Remote Control			Wired / Wireless	Wired / Wireless	Wired / Wireless	Wired / Wireless	Wired / Wireless	

**Optional Parts:**

IR Receiver Kit: UTY-LRHYA1 / UTY-LRHYA2 (24 / 36LR)  
 Fresh Air Intake Kit: UTZ-VXAA  
 Wired Remote Controller: UTB-YUD  
 Standard Wired Remote Controller (Three Wires): UTY-RNNYM (36LRLD-A / 45LRLD-A)  
 Human Sensor Kit: UTY-SHZXC (36LRLD-A / 45LRLD-A)  
 Fresh Air Intake: UTZ-VXRA (36LRLD-A / 45LRLD-A)

