



Model No.	Indoor Unit		ASYG09LU	ASYG12LU	ASAG09LM	ASAG12LM	ASAA09JG	ASAA12JG
Power Source			V/Ø/Hz 230 / 1 / 50	230 / 1 / 50	230 / 1 / 50	230 / 1 / 50	230 / 1 / 50	230 / 1 / 50
Air Flow	Cooling	H/M/L/Q	m³/h	600 / 550 / 470 / 330	660 / 600 / 530 / 330	600 / 520 / 430 / 310	660 / 560 / 450 / 310	750 / 610 / 440 / 300
Sound Pressure Level			dB(A)	36 / 32 / 28 / 21	37 / 34 / 31 / 21	37 / 33 / 29 / 21	40 / 36 / 30 / 21	43 / 38 / 32 / 22
Net Dimension H x W x D			mm	282 x 870 x 185	282 x 870 x 185	268 x 840 x 203	268 x 840 x 203	260 x 790 x 198
Weight			kg	9.5	9.5	8.5	8.5	7.5
Piping Connections	Liquid Ø	mm	Ø6.35 (1/4)	Ø6.35 (1/4)	Ø6.35 (1/4)	Ø6.35 (1/4)	Ø6.35 (1/4)	Ø6.35 (1/4)
	Gas Ø	(in)	Ø9.52 (3/8)	Ø9.52 (3/8)	Ø9.52 (3/8)	Ø9.52 (3/8)	Ø9.52 (3/8)	Ø9.52 (3/8)
Remote Control			Wireless	Wireless	Wireless	Wireless	Wireless	Wireless



(09)



Model No.	Indoor Unit		ASAG18JFCB	ASAG24JFCB	ASAG30JFTB
Power Source			V/Ø/Hz 230 / 1 / 50	230 / 1 / 50	230 / 1 / 50
Air Flow	Cooling	H/M/L/Q	m³/h	1,120 / 900 / 740 / 580	1,120 / 900 / 740 / 580
Sound Pressure Level			dB(A)	49 / 42 / 37 / 32	49 / 42 / 37 / 32
Net Dimension H x W x D			mm	320 x 998 x 238	340 x 1,150 x 280
Weight			kg	14	18
Piping Connections	Liquid Ø	mm	Ø6.35 (1/4)	Ø6.35 (1/4)	Ø9.52 (3/8)
	Gas Ø	(in)	Ø15.88 (5/8)	Ø15.88 (5/8)	Ø15.88 (5/8)
Remote Control			Wireless	Wireless	Wireless

